

# EF200-24R5

High flow filter fan



This vertical filter fan, EF, with a IP 54 protection degree, is easy to install thanks to its click-in feature. Unnecessary downtime is avoided, since water and dust are prevented from entering the enclosure through the filter, and the reliable fan motor will ensure constant ventilation.



IP 54 | TYPE 12

## 24 V DC

|                            |              |
|----------------------------|--------------|
| Bearing type               | Ball         |
| Connection                 | 310 mm cable |
| Current (A)                | 0.21         |
| Noise (dB)                 | 44           |
| EF+EFA Air flow (m³/h)     | 44/50        |
| Connection Type            | 1            |
| Unimpeded air-flow (m³/h)  | 61/67        |
| Filter mat (EN779)         | G4           |
| Filtration efficiency (%)  | >90          |
| Service life L10 (40°C)(h) | 62.500       |
| Cut-out (mm)               | 125 x 125    |
| Weight (kg)                | 0.45         |
| Power (W)                  | 5.00         |
| Fuse (A)                   | 6            |
| Item no.                   | EF200-24R5   |

**Description:** Filter fan for forced ventilation. nVent HOFFMAN filter fans save time on installation as they are installed with a click-in system without screws. The hinged front cover can be easily opened for quick and easy filter replacement. The airflow direction and the connection position can easily be changed.

**Material:** Front cover manufactured from injection-moulded thermoplastic, self-extinguishing, UL94V0.

**Temperature range:** -40 °C to +55 °C.

**Protection:** IP 54 | TYPE 12.

**Finish:** RAL 7035.

**Pack quantity:** One fan with filter.